

“PVC ESTENSIBILE” INKS

series 350

PRINT TYPE	Flexographic.
MAIN SUBSTRATE	PVC estensibile films.
RECOMMENDED THINNERS	Ethyl Acetate. Our specific diluent: “DILUENTE ET100” (“ET100 DILUENT”), code 100D/025.
RETARDER	Methoxypropanol (e.g. Dowanol PM), glycoethers (e.g. Cellosolve). Our specific retarder: “RITARDANTE PM100” (“PM100 RETARDER”), code 100D/013.
CLICHE’	Photopolymeric clichè can be used which have Ethyl Acetate fastness or butyl rubber rollers.
FEATURES	Inks suitable for estensibile PVC printing. Excellent printability and gloss, good scratch and rubbing resistance.
NOTES	Shake the ink before use.
EXPIRY DATE AND STORAGE	The quality of the product is ensured for 12 months from the manufacture date with the product kept in the original sealed containers. A storage temperature of 20°C is suggested.
STANDARD PACKAGING	Pails 20-25 Kg; drums 170 Kg; tanks 500-900 Kg.



*The aim of these technical data sheets is to inform the customers about our products, but they can not include all printing situations.
For this reason the particularities of all printing processes must be considered before use of the described products and we suggest to contact us for further informations.*